


Note:


1.Type C -Pin out is the same as this drawing.



REV	ECN#	DESCRIPTION OF REVISION	DRAW BY DATE	CHECK BY DATE	APPROVE BY DATE
A3	ECN-200615	Change Wire&Mylar Color	Lucas 06/12/20	Lucas 06/12/20	Ray 06/12/20



USB3.0 A MALE
MOLDED BLACK
(P1)




USB TYPE C M
RIGHT ANGLE RIGHT/LEFT
MOLDED BLACK
(P2)

PIN OUT

P1		P2
1	RED	A4,B4,A9,B9
2	WHITE	A7
3	GREEN	A6
4	BLACK	A1,B1,A12,B12
5	BLUE(YELLOW MYLAR)	A3
6	YELLOW(YELLOW MYLAR)	A2
7	DRAIN	
8	BLUE(GREEN MYLAR)	B10
9	YELLOW(GREEN MYLAR)	B11
SHELL	DRAIN+BRAID	SHELL

RESISTOR & CAPACITOR



P/N	LENGTH
RR-ASCH-08GRCHF	203 ⁺²⁰ ₋₀
RR-ASCH-75GRCHF	1905 ⁺⁶⁰ ₋₀
RR-ASCH-177GRCHF	4496±50

TITLE USB3.0 AM TO USB3.1 C TYPE MALE RIGHT ANGLE RIGHT/LEFT						DRAWING NUMBER RR-ASCH-XXGRCHF				REV. A3
 DO NOT SCALE DRAWINGS	B	1:1	Lucas 03/27/19	Lucas 03/27/19	Ray 03/27/19	X.X ± 0.5 X.XX ± 0.2	X.XXX ± 0.05 ANGLES ± 1°	mm	1/3	
THIRD ANGLE PROJECTION	SIZE	SCALE	DRAW / DATE	CHECK / DATE	APPROVE / DATE	TOLERANCES		UNIT	SHEET	

USB FIREWIRE .com

THE INFORMATION CONTAINED HEREIN IS PROPRIETARY AND CONFIDENTIAL TO RR BUSINESS VENTURES, LLC. THE POSSESSOR AGREES TO THE FOLLOWING

1. MAINTAIN THIS DOCUMENT IN CONFIDENCE
2. NOT TO REPRODUCE OR COPY IT
3. NOT TO REVEAL OR PUBLISH IT IN WHOLE OR PART

1

2

3

4

REV	ECN#	DESCRIPTION OF REVISION	DRAW BY DATE	CHECK BY DATE	APPROVE BY DATE
A3	ECN-200615	Change Wire&Mylar Color	Lucas 06/12/20	Lucas 06/12/20	Ray 06/12/20

***CONSTRUCTION:

1.CABLE: * UL2725 (30#/1PR+EAM)*2+30#/1PR+24#/2C+FEP TAPE+S90% OD:5.0mm
BLACK PVC JACKET.

***CONNECTOR:

2.USB A/M: * USB A "3.0" TYPE 9PIN MALE SOLDER TYPE.(NEW-CONN P/N:06801508M5CA)
* PINS: 30u GOLD PLATED OVER NICKEL.
* INSULATOR: BLUE COLOR P.B.T UL 94V-0 RATED.
* SHELL: STEEL WITH GOLD FLASH .
* MOLDED: BLACK PVC 45P.

3.USB C/M: * USB TYPE C MALE SOLDER TYPE.
* PINS: 30u GOLD PLATED OVER NICKEL.
* INSULATOR: BLACK THERMOPLASTIC UL 94V-0.
* SHELL: STEEL WITH GOLD FLASH.
* RESISTOR(56KΩ) AND CAPACITOR.
* MOLDED: BLACK PVC 45P & 30P.

4.TEST: * CT: 2 ohm IS: 5M ohm DC300V 0.1S

5.PACKING: * PACK EACH CABLE IN A POLY BAG AND 25PCS IN A POLY BAG.

6.MATERIAL: * MATERIAL WITH RoHS GRADE.



TITLE USB3.0 AM TO USB3.1 C TYPE MALE RIGHT ANGLE RIGHT/LEFT					DRAWING NUMBER RR-ASCH-XXGRCHF			REV. A3	
 DO NOT SCALE DRAWINGS	B	1:1	Lucas 03/27/19	Lucas 03/27/19	Ray 03/27/19	X.X ± 0.5 X.XX ± 0.2	X.XXX ± 0.05 ANGLES ± 1°	mm	2/3
THIRD ANGLE PROJECTION	SIZE	SCALE	DRAW / DATE	CHECK / DATE	APPROVE / DATE	TOLERANCES		UNIT	SHEET



THE INFORMATION CONTAINED HEREIN IS PROPRIETARY AND CONFIDENTIAL TO RR BUSINESS VENTURES, LLC. THE POSSESSOR AGREES TO THE FOLLOWING
1. MAINTAIN THIS DOCUMENT IN CONFIDENCE
2. NOT TO REPRODUCE OR COPY IT
3. NOT TO REVEAL OR PUBLISH IT IN WHOLE OR PART

1

2

3

4

1

2

3

4


REV	ECN#	DESCRIPTION OF REVISION	DRAW BY DATE	CHECK BY DATE	APPROVE BY DATE
A3	ECN-200615	Change Wire&Mylar Color	Lucas 06/12/20	Lucas 06/12/20	Ray 06/12/20

P/N	LENGTH(mm)	PE BAG(Inch)	PACKAGE
RR-ASCH-08GRCHF	203 ⁺²⁰ ₋₀	5.5"*10	(1)
RR-ASCH-75GRCHF	1905 ⁺⁶⁰ ₋₀	5.5"*10	(3)
RR-ASCH-177GRCHF	4496±50	7*10	(3)

PE BAG LABEL




RoHS LABEL




NOTES:PACK EACH CABLE IN A POLY BAG
AND 25PCS IN A POLY BAG.



PACK(1)



PACK(2)



PACK(3)



TITLE
USB3.0 AM TO USB3.1 C TYPE MALE RIGHT ANGLE RIGHT/LEFT

DRAWING NUMBER
RR-ASCH-XXGRCHF

REV.
A3

DO NOT SCALE DRAWINGS	B	1:1	Lucas 03/27/19	Lucas 03/27/19	Ray 03/27/19	X.X ± 0.5 X.XX ± 0.2	X.XXX ± 0.05 ANGLES ± 1°	mm	3/3
THIRD ANGLE PROJECTION	SIZE	SCALE	DRAW / DATE	CHECK / DATE	APPROVE / DATE	TOLERANCES		UNIT	SHEET



THE INFORMATION CONTAINED HEREIN IS PROPRIETARY
AND CONFIDENTIAL TO RR BUSINESS VENTURES, LLC. THE
POSSESSOR AGREES TO THE FOLLOWING
1. MAINTAIN THIS DOCUMENT IN CONFIDENCE
2. NOT TO REPRODUCE OR COPY IT
3. NOT TO REVEAL OR PUBLISH IT IN WHOLE OR PART